

AMP | AMP CPC

TE Internal #: 206151-2

Circular Power Connectors, Housing, 600 VDC, Wire-to-Wire, 37

Position, Wire & Cable, Receptacle, Pin, Power & Signal, Black, All

Plastic, AMP CPC

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors > Cable/Panel Mount Connector, CPC Series 1











Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 37

Sealable: No

All Cable/Panel Mount Connector, CPC Series 1 (57)

Features

Product Type Features

Connector Product Type	Housing
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle
Circular Connector Shell Type	All Plastic

Configuration Features

Reverse Numbering	Without
Number of Positions	37
Number of Power Positions	0
Number of Signal Positions	37

Electrical Characteristics



Operating Voltage	600 VAC
Contact Features	
Reverse Gender	No
Contact Type	Pin
Contact Protection	With
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Mating Retention Type	Threaded Coupling
Screw & Hole Thread Size	1-3/8 - 18 UNEF-2A
Polarization Code	A
Connector Mounting Type	Cable Mount (Free-Hanging)
Mating Retention	With
Panel Mount Feature	Without
Housing Features	
Housing Features Body Orientation	Straight
	Straight Black
Body Orientation	
Body Orientation Housing Color	Black
Body Orientation Housing Color Housing Material Circular Connector Shell Size	Black Thermoplastic
Body Orientation Housing Color Housing Material Circular Connector Shell Size	Black Thermoplastic
Body Orientation Housing Color Housing Material Circular Connector Shell Size Usage Conditions	Black Thermoplastic 23
Body Orientation Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance	Black Thermoplastic 23 -55 - 105 °C[-67 - 221 °F]
Body Orientation Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance	Black Thermoplastic 23 -55 - 105 °C[-67 - 221 °F]
Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application	Black Thermoplastic 23 -55 – 105 °C[-67 – 221 °F] None
Body Orientation Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded	Black Thermoplastic 23 -55 – 105 °C[-67 – 221 °F] None Power & Signal
Body Orientation Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application	Black Thermoplastic 23 -55 – 105 °C[-67 – 221 °F] None Power & Signal
Body Orientation Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards UL Flammability Rating	Black Thermoplastic 23 -55 – 105 °C[-67 – 221 °F] None Power & Signal No
Body Orientation Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards	Black Thermoplastic 23 -55 – 105 °C[-67 – 221 °F] None Power & Signal No

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-AM71-C83998B CPC Cable Clamps



TE Part # 206150-1 CPC PLUG ASSEMBLY SIZE 23-37



TE Part # 207299-4 FLANGE PLUG





TE Part # 206150-2 CPC PLUG,SZ 23-37,SMALL PACK



TE Part # 207055-1 EXTENDER BACK SHELL



CAP, CPC, SIZE 23 RECP, ORANGE









Also in the Series | AMP CPC



Circular Connector Adapters(7)



Circular Connector Boots & Strain Relief(6)



Circular Connector Caps & Covers(16)



Circular Connector Hardware(3)



Circular Connector Keying Plugs(2)



Circular Connector Seals(36)



Circular Power Connectors(460)



Insertion & Extraction Tools(1)



Power Contacts(6)



Sealing Sleeves(2)



Unscreened Circular Connector Backshells & Clamps(56)

Customers Also Bought











TE Part #2-968696-3

TE Part #955-621-101

TE Part #1599381-1

CABLE ASSY FAKRA B-F x2

CHRISTMAS TREE

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_206151-2_AG.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_206151-2_AG.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_206151-2_AG.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English